



SAFETY DATA SHEET
ISOCLENE

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME ISOCLENE
PRODUCT NO. AISO250, 01L
APPLICATION Cleaning Product
SUPPLIER AF INTERNATIONAL. A division
of HK WENTWORTH LTD
KINGSBURY PARK.
MIDLAND ROAD,
SWADLINCOTE
DERBYSHIRE DE11 0AN
UNITED KINGDOM
+44 (0) 1283 222111
+44 (0) 1283 550177
info@hkw.co.uk
EMERGENCY TELEPHONE +44(0)1283 222 111 between 8.30 am - 5.00pm Mon - Fri

2 HAZARDS IDENTIFICATION

Highly flammable.

Vapours may cause drowsiness and dizziness.

Irritating to eyes.

CLASSIFICATION Xi;R36. F;R11. R67.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
PROPAN-2-OL	200-661-7	67-63-0	80-100%	F;R11 Xi;R36 R67

The Full Text for all R-Phrases are Displayed in Section 16

COMPOSITION COMMENTS

Ingredients not listed are classified as non-hazardous or at a concentration below reportable levels

4 FIRST-AID MEASURES

NOTES TO THE PHYSICIAN

Treat symptomatically

INHALATION

Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

INGESTION

DO NOT INDUCE VOMITING! Rinse mouth thoroughly. Get medical attention.

SKIN CONTACT

Promptly wash contaminated skin with soap or mild detergent and water. Promptly remove clothing if soaked through and wash as above. Get medical attention if irritation persists after washing.

EYE CONTACT

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

5 FIRE-FIGHTING MEASURES

ISOCLENE

EXTINGUISHING MEDIA

Use: Alcohol resistant foam. Powder. Dry chemicals, sand, dolomite etc.

SPECIAL FIRE FIGHTING PROCEDURES

Move container from fire area if it can be done without risk. Use water to keep fire exposed containers cool and disperse vapours.

6 ACCIDENTAL RELEASE MEASURES

SPILL CLEAN UP METHODS

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Wear necessary protective equipment. Absorb in vermiculite, dry sand or earth and place into containers.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact.

STORAGE PRECAUTIONS

Flammable/combustible - Keep away from oxidisers, heat and flames. Store in tightly closed original container in a dry, cool and well-ventilated place. Keep in original container.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	TWA - 8 hrs		STEL - 15 min		Notes
PROPAN-2-OL	WEL	400 ppm	999 mg/m ³	500 ppm	1250 mg/m ³	

WEL = Workplace Exposure Limit.

INGREDIENT COMMENTS

WEL = Workplace Exposure Limits

PROTECTIVE EQUIPMENT



ENGINEERING MEASURES

All handling to take place in well-ventilated area.

RESPIRATORY EQUIPMENT

No specific recommendation made, but respiratory protection must be used if the general level exceeds the Recommended Workplace Exposure Limit.

HAND PROTECTION

Use protective gloves. The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material.

EYE PROTECTION

Wear approved, tight fitting safety glasses where splashing is probable.

OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet.

Wash promptly with soap & water if skin becomes contaminated. When using do not eat, drink or smoke.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Liquid		
COLOUR	Colourless		
ODOUR	Characteristic		
BOILING POINT (°C)	82	RELATIVE DENSITY	0.785 @ 20 °c
VAPOUR DENSITY (air=1)	2.8	VAPOUR PRESSURE	4.40 kPa @ 20 °c
EVAPORATION RATE	2.93	VISCOSITY	n/a cSt @ 20 °c

ISOCLENE

FLASH POINT (°C)	12 OC (Open cup).	AUTO IGNITION TEMPERATURE (°C)	425
FLAMMABILITY LIMIT - LOWER(%)	2.50	FLAMMABILITY LIMIT - UPPER(%)	12.70

10 STABILITY AND REACTIVITY

STABILITY

Stable under normal temperature conditions.

CONDITIONS TO AVOID

Avoid heat, flames and other sources of ignition.

MATERIALS TO AVOID

Strong oxidising substances.

11 TOXICOLOGICAL INFORMATION

INHALATION

May cause irritation to the respiratory system.

INGESTION

May cause stomach pain or vomiting.

SKIN CONTACT

Prolonged contact may cause dryness of the skin. Acts as a defatting agent on skin. May cause cracking of skin, and eczema.

EYE CONTACT

Irritating to eyes.

ROUTE OF ENTRY

Skin absorption. Ingestion. Skin and/or eye contact.

TARGET ORGANS

Central nervous system. Eyes. Respiratory system, lungs. Skin.

MEDICAL SYMPTOMS

Irritation of eyes and mucous membranes. Dilated pupils. Rhinitis (inflammation of the nasal mucous membranes). Upper respiratory irritation. General respiratory distress, unproductive cough. Skin irritation. Central nervous system depression. Drowsiness, dizziness, disorientation, vertigo.

Name	PROPAN-2-OL
Toxic Dose 1 - LD 50	5045 mg/kg (oral rat)
Toxic Dose 2 - LD 50	3600 mg/kg (oral-mouse)
Toxic Conc. - LC 50	47-73 mg/l/4h (inh-rat)

12 ECOLOGICAL INFORMATION

ECOTOXICITY

Not regarded as dangerous for the environment.

Name	PROPAN-2-OL
LC 50, 96 Hrs, FISH mg/l	9600
EC 50, 48 Hrs, DAPHNIA, mg/l	10000

13 DISPOSAL CONSIDERATIONS

DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements. Absorb in vermiculite or dry sand, dispose in licensed hazardous waste.

14 TRANSPORT INFORMATION



ISOCLENE

UK ROAD CLASS	3		
PROPER SHIPPING NAME	ISOPROPANOL (ISOPROPYL ALCOHOL)		
UN NO. ROAD	1219	UK ROAD PACK GR.	II
ADR CLASS NO.	3	ADR CLASS	Class 3: Flammable liquids.
ADR PACK GROUP	II	HAZARD No. (ADR)	33
ADR LABEL NO.	3	HAZCHEM CODE	2YE
CEFIC TEC(R) NO.	30GF1-I+II	RID CLASS NO.	3
RID PACK GROUP	II	UN NO. SEA	1219
IMDG CLASS	3	IMDG PAGE NO.	3
IMDG PACK GR.	II	EMS	F-E, S-D
MFAG	See Guide	MARINE POLLUTANT	No.
UN NO. AIR	1219	AIR CLASS	3
AIR PACK GR.	II		

15 REGULATORY INFORMATION

SYMBOLS



Irritant



Highly Flammable

RISK PHRASES

R11	Highly flammable.
R36	Irritating to eyes.
R67	Vapours may cause drowsiness and dizziness.

SAFETY PHRASES

S9	Keep container in a well-ventilated place.
S16	Keep away from sources of ignition - No smoking.
S25	Avoid contact with eyes.
S26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S51	Use only in well-ventilated areas.

UK REGULATORY REFERENCES

Chemicals (Hazard Information & Packaging) Regulations.

The Control of Substances Hazardous to Health Regulations 1988.

EU DIRECTIVES

System of specific information relating to Dangerous Preparations. 2001/58/EC.

Dangerous Substance Directive 67/548/EEC.

Dangerous Preparations Directive 1999/45/EC.

Commission Directive 2000/39/EC of 8 June 2000 establishing a first list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work.

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments.

APPROVED CODE OF PRACTICE

Classification and Labelling of Substances and Preparations Dangerous for Supply. Safety Data Sheets for Substances and Preparations.

GUIDANCE NOTES

Workplace Exposure Limits EH40.

ISOCLENE

16 OTHER INFORMATION

REVISION COMMENTS

Revised in accordance with CHIP3 and EU Directives 1999/45/EC and 2001/58/EC

ISSUED BY

Helen O'Reilly

REVISION DATE

MAY 2008

REV. NO./REPL. SDS

1

GENERATED

SDS NO.

10636

RISK PHRASES IN FULL

R11

Highly flammable.

R36

Irritating to eyes.

R67

Vapours may cause drowsiness and dizziness.